

## 2-DOOR REFRIGERATED CABINET, HC ADVANCE K 140-4 L

Product Serie: Advance

Artikelnummer: 131141070



Hoshizaki ADVANCE is a series of durable refrigeration and freezer cabinets, exceeding the requirements of demanding commercial kitchen environments.

The Advance K 140-4 L is a 2-Door Refrigerated Cabinet, HC with a net internal volume of 797 liters. The outside dimensions are mm.

### DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

### MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

### HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

### MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

### UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

### TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.

## SPECIFICATIES

<b>Productnaam</b>	2-Door Refrigerated Cabinet, HC
<b>Temperatuurbereik</b>	0/+10°C
<b>Inhoud, bruto (liter)</b>	1200
<b>Netto bruikbaar volume (liter)</b>	797
<b>Inwendig</b>	RvS
<b>Afmetingen W x D x H (mm)</b>	1344 x 830 x 2000
<b>Gewicht, verpakt (kg)</b>	192
<b>Koelmiddel</b>	R290
<b>GWP</b>	3
<b>Aansluiting</b>	230V, 50 Hz
<b>Aansluitwaarde (Watt)</b>	270
<b>Energie verbruik Ecodesign (kWh)</b>	926
<b>Energie Efficiëntieklasse</b>	C
<b>Energie Efficiëntie Index EEI</b>	48.32

<b>Geluidsniveau – dB(A)</b>	53
<b>Isolatie (mm)</b>	60 mm (polyurethaan)
<b>Koelcapaciteit bij -25°C (Watt)</b>	632
<b>Klimaatklasse</b>	5
<b>GN – Shelf size</b>	2/1 GN diep
<b>Deur type</b>	Geïsoleerde deur
<b>Poten / Wielen</b>	H = 130/180 mm (L)
<b>Uitwendig</b>	RvS
<b>Koelmiddel (kg)</b>	0.085
<b>CO<sub>2</sub> Equivalent (kg)</b>	0.255
<b>Uitgerust met</b>	One right and one left hand hinged door with lock, self closing doors, 8 grey shelves, LED lighting
<b>Maximaal aantal roosters</b>	22 x 2, distance of 57 mm
<b>Aantal roosters</b>	8