



# 1-DOOR FREEZER CABINET, HC PREMIER F 60 L DR

**Product Serie: Premier** Artikelnummer: 173601010

The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 5), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stabile stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into lowceiling environments, yet convince with a surprisingly high internal volume. The Premier F 60 L DR is a 1-Door Freezer Cabinet, HC with a net internal volume of 335. The dimensions are  $610 \times 920 \times 10^{-2}$ 2080-2130 mm

#### "FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. Additionally, the automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal and reduce escaping of cold air.

COMPARTMENTALIZED DESIGN The PREMIER's condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it can easily be serviced via the front flap on top of the cabinet.

#### LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier F 60 L DR runs on natural refrigerant and

#### **ERGONOMIC & EASY TO USE**

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real-time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

### **HYGIENE & WASTE REDUCTION**

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The Interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

#### EASY CUSTOMIZATION & FLEXIBILITY PREMIER

cabinets can easily be adjusted to your requirements, for example, the length of the legs, the position of the door, and the foot pedal. They also can accommodate shelves up to 18-22 levels (4 shelves included) offering you high flexibility to accommodate different types of produce.

## **SPECIFICATIES**

Temperatuurbereik -25/-5°C  Inhoud, bruto (liter) 480  Netto bruikbaar volume (liter) 335  Inwendig RvS AISI 304  Afmetingen W x D x H (mm) 610 x 920 x 2080-2130  Gewicht, verpakt (kg) 120  Koelmiddel R290  GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)  Energie Efficiëntie Index EEI 48.23	Productnaam	1-Door Freezer Cabinet, HC
Netto bruikbaar volume (liter) 335  Inwendig RvS AISI 304  Afmetingen W x D x H (mm) 610 x 920 x 2080-2130  Gewicht, verpakt (kg) 120  Koelmiddel R290  GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Temperatuurbereik	-25/-5°C
Inwendig RvS AISI 304  Afmetingen W x D x H (mm) 610 x 920 x 2080-2130  Gewicht, verpakt (kg) 120  Koelmiddel R290  GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Inhoud, bruto (liter)	480
Afmetingen W x D x H (mm) 610 x 920 x 2080-2130  Gewicht, verpakt (kg) 120  Koelmiddel R290  GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Netto bruikbaar volume (liter)	335
Gewicht, verpakt (kg)  Koelmiddel  R290  GWP  3  Aansluiting  230V, 50 Hz  Aansluitwaarde (Watt)  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Inwendig	RvS AISI 304
Koelmiddel R290  GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Afmetingen W x D x H (mm)	610 x 920 x 2080-2130
GWP 3  Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh) 1506  Energie Efficiëntieklasse (ISO 22041-2019) C	Gewicht, verpakt (kg)	120
Aansluiting 230V, 50 Hz  Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO 22041-2019)	Koelmiddel	R290
Aansluitwaarde (Watt) 520  Energie verbruik Ecodesign (kWh) 1506  Energie Efficiëntieklasse (ISO C 22041-2019)	GWP	3
Energie verbruik Ecodesign (kWh)  Energie Efficiëntieklasse (ISO C 22041-2019)	Aansluiting	230V, 50 Hz
(kWh)  Energie Efficiëntieklasse (ISO C 22041-2019)	Aansluitwaarde (Watt)	520
22041-2019)		1506
Energie Efficiëntie Index EEI 48.23		С
	Energie Efficiëntie Index EEI	48.23

Geluidsniveau – dB(A)	50
Isolatie (mm)	80 mm (polyurethane)
Koelcapaciteit bij -25°C (Watt)	376
Klimaatklasse	5
GN - Shelf size	1/1 GN diep
Deur type	Geïsoleerde deur
Poten / Wielset	H = 130/180 mm (L)
Uitwendig	RvS AISI 304
Koelmiddel (kg)	0.085
CO2 Equivalent (kg)	0.255
Uitgerust met	Right hand hinged reversible door with lock, automatic door closing, pedal door opener, 4 grey shelves, LED lighting
Maximaal aantal roosters	25, distance of 57 mm
Aantal roosters	4