

1-DOOR REFRIGERATED CABINET, HC PREMIER KG 60 L DR

Product Serie: Premier

Artikelnummer: 174601010



The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 4), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stable stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into low-ceiling environments, yet convince with a surprisingly high internal volume. The Premier KG 60 L DR is a 1-Door Refrigerated Cabinet, HC with a net internal volume of 335. The dimensions are 610 x 920 x 2080-2130 mm.

"FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. Additionally, the automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal and reduce escaping of cold air.

COMPARTMENTALIZED DESIGN The PREMIER's condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it can easily be serviced via the front flap on top of the cabinet.

LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier KG 60 L DR runs on natural refrigerant and has [4].

ERGONOMIC & EASY TO USE

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real-time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

HYGIENE & WASTE REDUCTION

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The Interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

EASY CUSTOMIZATION & FLEXIBILITY PREMIER

cabinets can easily be adjusted to your requirements, for example, the length of the legs, the position of the door, and the foot pedal. They also can accommodate shelves up to 18-22 levels (4 shelves included) offering you high flexibility to accommodate different types of produce. "

SPECIFICATIES

Productnaam	1-Door Refrigerated Cabinet, HC
Temperatuurbereik	+2/+12°C
Inhoud, bruto (liter)	480
Netto bruikbaar volume (liter)	335
Inwendig	RvS AISI 304
Afmetingen W x D x H (mm)	610 x 920 x 2080-2130
Gewicht, verpakt (kg)	125
Koelmiddel	R600a
GWP	3
Aansluiting	230V, 50 Hz
Aansluitwaarde (Watt)	120
Energie verbruik Ecodesign (kWh)	373
Energie Efficiëntieklasse (ISO 22041-2019)	B
Energie Efficiëntie Index EEI	32.2

Geluidsniveau – dB(A)	46
Isolatie (mm)	80 mm (polyurethane)
Koelcapaciteit bij -10°C (Watt)	206
Klimaatklasse	4
GN – Shelf size	1/1 GN diep
Deur type	Glasdeur
Poten / Wielset	H = 130/180 mm (L)
Uitwendig	RvS AISI 304
Koelmiddel (kg)	0.08
CO2 Equivalent (kg)	0.24
Uitgerust met	Right hand hinged reversible glass door with lock, automatic door closing, pedal door opener, 4 grey shelves, LED lighting
Maximaal aantal roosters	25, distance of 57 mm
Aantal roosters	4